

Shell's EOR Journey: Experiences past to present


ANP Workshop 23-24 March 2017

Dr Stephen Goodyear


EOR Deployment Lead, Principal Technical Expert Gas EOR and Storage Solutions

- Shell's EOR Journey
- Maximising economic recovery
- EOR challenges and enablers
- Onshore to offshore
- Offshore CO₂ EOR
- Conclusions


EOR journey - Learning by doing



EOR - R&D to Deployment




Polymer flood - Marmul



- Heterogeneous clastic reservoir 90 cp oil
- Large scale polymer flood on-stream 2010
 - 17,500 m³/day (polymer)
 - Low salinity injection water (5000ppm TDS)
 - 27 patterns
- Oil Increase/Water cut reversal observed
 - Produced polymer can be handled
- Increase from 27 → 46 injectors since May 2015
- Urban planning, rotation schedule prepared for full field implementation



Copyright of Shell Upstream International







Steam Injection - Belridge and Aera

- Belridge Tulare core of Aera, STOIIP 1.6 bstb
 - Started production 1911, water drive reached watercuts above 90% before conversion to steam flooding
 - Large scale steam injection began 1982
 - Ongoing conversion of deeper reservoirs from waterflood to steamflood
 - Manages a stock of some 15000 wells at an average production rate of <10bopd.
 - In current environment Aera still able to make a profit









Aera Energy LLC – Development Team

10000 Ming Ave. Bakersfield CA 93311

www.aeraenergy.cor

Company Contact Person: Greg L. Williams, Lean Advisor

Office 661-665-5549 Cell 661-340-9593 glwilliams@aeraenergy.con

CO₂ EOR – Denver Unit

Largest CO₂ EOR project in the world, developed by Shell

- more than 400 MMscf/d sustained CO₂ injection in >100 patterns
- over 200 MMscf/d gas processing/recycling on site
- surveillance and management of CO₂ EOR



Authorpogenic CO, Ustard CO.

On Processing State of Co.

Bases Bod CO, Corpeny

Author Dollar State of Co.

Bases Bod CO, Corpeny

Author CO.

Sources

Plans

Bases Bod CO, Corpeny

Author CO.

Sources


Plans

Bases Bod CO, Corpeny


Author CO.

Sources

Plans



EOR projects in Oman



- Shell's EOR Journey
- Maximising economic recovery
- EOR challenges
- Onshore to offshore
- Offshore CO₂ EOR
- Conclusions

Maximising economic oil recovery

Not mobile to waterflood

Mobile to waterflood

Reserves

Produced

Operational Excellence

EOR
Chemical
Gas
Thermal

WRFM
Infill drilling
Throughput

■ A field with 35% ultimate recovery leaves almost twice as much oil in the ground as we have produced

Where
is the remaining oil in
the
reservoir?

Why
is oil currently trapped
in these locations?

How
could optimised IOR and
EOR techniques recover
additional oil?

Secondary

Primary

- Shell's EOR Journey
- Maximising economic recovery
- EOR challenges
- Onshore to offshore
- Offshore CO₂ EOR
- Conclusions

The EOR challenge and enablers

EOR is not business as usual, it is hard work technically and commercially


- Less oil to go after
 - 10-20% EOR incremental, vs 30-60% primary/secondary recovery
- Slower response times
- More expensive injectants
- Requirement for more surface facilities with added complexity

Enablers

- Lifecycle planning and surface subsurface integration
- Step up in surveillance capability to drive performance
- Contracting and procurement framework and standardisation
- Excellent stakeholder management
- Appropriate fiscal and regulatory structures needed

EOR systems: Integration

- Integration of subsurface and surface underpins successful EOR projects
 - Work on full injection/production cycle
- Injection system to achieve injectant at design specification in reservoir and flexibility to optimise EOR performance
- Production system robust to changes in fluid streams through EOR project lifecycle



ANP Workshop

EOR reservoir surveillance

Fahud - Thermal Gas Oil Gravity Drainage


Caprock integrity

Interpretation of microseismic events
Traffic light classification
Geomechanical modeling to support interpretation


Steam front conformance

Geomechanical inversion of deformation data

Steam Distribution and Caprock Integrity Monitoring



Surface deformation




Steam Distribution Monitoring

oledii bisiibolidi Melik



Amal – Steam Drive
Steam front conformance: Integrated interpretation of seismic, petrophysical (log) and geological data

Understanding of preferential steam direction caused by intra Haradh channel system



Temperature Logging




Steam outline Constrained by data




Marmul – Polymer Injection
Fracture monitoring and control
Classification of wells in traffic light
surveillance priority
well test interpretation

calibration and modeling leading to water treatment decisions

Frac Length Monitoring



Pressure fall off test – Identification of Polymer Front



FracIT Modelling of frac length



Greater - Birba Miscible Gas Injection
Gas inflow monitoring
DTS feasibility and design

- Shell's EOR Journey
- Maximising economic recovery
- EOR challenges
- Onshore to offshore
- Offshore CO₂ EOR
- Conclusions

Moving EOR offshore



Additional challenges for offshore EOR compared to onshore EOR

- Wider well spacing and slower reservoir processing rates
- Limitations on weight and space for additional facilities or storage
- Impact of EOR injectants on wells/facilities (corrosion, non-metallic materials)
- Impact of wells/facilities on EOR injectants (corrosion products, shear)
- Design life of facilities
- Surveillance challenged, especially for sub-sea wells

Approaches

- Day 1 EOR implementation
- Lifecycle planning to create future EOR optionality
- Brown field modification, potentially supported by additional jackets or vessels
- "Greenfield" EOR redevelopment with new facilities fit for 30+ years production

Status of Shell offshore EOR



- Operating/In execution
- Concept selected
 - Pre-feasibility
- Technology demonstration

Copyright of Shell Upstream International

St Joseph field: Surfactant polymer flooding for offshore

- St Joseph field identified as target for chemical **EOR**
- Full field ASP concept feasibility assessment
 - Water treatment and logistics were large cost and operational challenge
- Shift development concept to SP
 - No need to remove divalents from water, but at expense of higher concentration of polymer and surfactants
 - Proved in a SWCTT that SP has the same oil recovery efficiency as ASP
- Can only make things work by working them in

ANP Workshop






- Shell's EOR Journey
- Maximising economic recovery
- EOR challenges
- Onshore to offshore
- Offshore CO₂ EOR
- Conclusions

Offshore tertiary CO₂ EOR

- Shell has been active in pushing next generation CO₂ EOR projects
- Studies show offshore CO₂ EOR can be technically and economically feasible
 - HSSE brings new issues
 - Subsurface-surface integration key
 - Innovation needed to simplify facilities and reduce CAPEX and OPEX
- Commercially attractive projects require:
 - Reservoirs with large enough EOR prize
 - CO₂ supply (volume and price)
 - Supportive regulatory and fiscal regimes

"Brownfield" Halten value chain




CO₂ HSSE offshore

Safe operation first priority

- Significant experience of CO₂ operations for onshore EOR projects
- Operation of CO₂ EOR offshore will introduce new set of challenges
 - Inventory, pressure, confined spaces, evacuation

■ Shell CO₂ release testing programme to evaluate and validate hazards



Key messages


Shell has pioneered EOR technology and continues to innovate to improve existing commercial processes, mature new technology and expand the range of application


- Commercially proven EOR solutions exist for onshore application
 - Technically robust
 - Appropriate regulatory frameworks
- Pushing the envelope of EOR deployment by looking to offshore applications
 - Significant technical and commercial challenges
 - Subsurface-surface integration key
 - Most progress made with gas based EOR in shallow and deep water environments



Shell Integrated CO₂ gas lift system

- Alternative to ESP systems
- Use CO₂ for lift gas, insert string or dual string to protect casing from corrosion
- Lift gas rate adjusted in response to changes in back produced gas
- Advantages
 - Simple and robust system using recycle system,
 only modest increase in capacity needed
 - Intrinsic risk management, flexibility over number of wells to be gas lifted and response to gas breakthrough timing
 - Reduced requirement for well workovers





Time

Three IOR/EOR questions: Where, Why and How?

Where
is the remaining oil in the
reservoir?

Why is oil currently trapped in these locations?

How
could optimised IOR and
EOR techniques recover
additional oil?

Redevelopment options need to be based on a proper understanding of the location of the remaining oil saturation

- Describe the location of the remaining oil (after depletion or waterflooding)
- Interpret reservoir performance to understand interplay of geology and balance of viscous and gravity forces
- Infill drilling, waterflood, throughput, deployable EOR processes

RESTRICTED